



Heavy duty rotation motor(s) with shock protection.

(Two rotation motors from DRG-25 standard, DRG 17-22 optional)

Delta-Box frame with robust end stops grab open.

Load safety valve intergrated in oil distributor.

Filters in rotation circuit.

Double roller ring (from DRG-28).

Hydraulic cylinder end damping.

Grease sealed wide pivot points prevent the ingress of debris.

Bolt on blades.



Type	DRG-14	DRG-15	DRG-17	DRG-19	DRG-22	DRG-25	DRG-27	DRG-28	DRG-36	DRG-45	DRG-65
Carrier weight*	10-18 ton	12-20 ton	12-24 ton	13-25 ton	15-30 ton	18-28 ton	20-30 ton	24-40 ton	30-50 ton	35-60 ton	50-80 ton
Weight (approx.)**	860 kg	900 kg	1030 kg	1120 kg	1315 kg	1400 kg	1480 kg	1820 kg	2210 kg	2330 kg	4165 kg
Capacity	340 l	415 l	365 l	480 l	570 l	650 l	760 l	825 l	960 l	1075 l	1660 l
Closing force	43 kN	43 kN	50 kN	50 kN	56 kN	60 kN	60 kN	70 kN	80 kN	80 kN	140 kN

Dimensions	DRG-14	DRG-15	DRG-17	DRG-19	DRG-22	DRG-25	DRG-27	DRG-28	DRG-36	DRG-45	DRG-65
Opening	1730 mm	1730 mm	1757 mm	1895 mm	1992 mm	2050 mm	2050 mm	2193 mm	2325 mm	2355 mm	2700 mm
Width	750 mm	900 mm	850 mm	1000 mm	1000 mm	1000 mm	1200 mm	1100 mm	1250 mm	1400 mm	1500 mm
Height	1228 mm	1228 mm	1225 mm	1256 mm	1340 mm	1380 mm	1380 mm	1393 mm	1481 mm	1496 mm	1818 mm

Hydraulic	DRG-14	DRG-15	DRG-17	DRG-19	DRG-22	DRG-25	DRG-27	DRG-28	DRG-36	DRG-45	DRG-65
Opening/Closing P _{max}	350 bar	350 bar	350 bar	350 bar	350 bar	350 bar	350 bar	350 bar	350 bar	350 bar	350 bar
Flow	80 l/min	80 l/min	100 l/min	100 l/min	100 l/min	100 l/min	100 l/min	120 l/min	120 l/min	120 l/min	200 l/min
Rotation P _{max}	140 bar	140 bar	140 bar	140 bar	140 bar	140 bar	140 bar	140 bar	140 bar	140 bar	140 bar
Flow	40 l/min	40 l/min	40 l/min	40 l/min	40 l/min	40-60 l/min	40-60 l/min	40-60 l/min	40-60 l/min	40-60 l/min	40-60 l/min

DRG-07-17-EN *Depending on capacity of carrier **Weight excluding bracket

Subject to change without notice.

Trendsetter in Demolition and Recycling Equipment

DEMAREC
 Demolition and Recycling Equipment BV
 De Hork 32 • 5431 NS Cuijk • The Netherlands
 Tel. +31(0)485 442300 • E-mail: info@demarec.com

demarec.com